

SAFETY CREWGUARD® STEEL TOE SB SRC

MEN'S/WOMEN'S: BLACK 53 • SIZE: XXS-XXL • EN ISO 20345:2011



Rubber upper

Rubber lining

Weight
(per shoe):
323 grams

WATER RESISTANT
designed to repel water and
keep your foot dry.



CE CERTIFIED SB SRC
according to
EN ISO 20345:2011
standards

STEEL SAFETY TOE - 200 joules


Wide fit



CLOG-RESISTANT OUTSOLE

- Added depth for improved durability and wear time.
- Larger surface area covered by the outsole provides better slip-resistance.
- Clog-resistant traction lugs have wide spacing which won't let dirt and debris get stuck in the outsole.

SFC GREATLY EXCEEDS INDUSTRY STANDARDS



**Superior
SFC SLIP-RESISTANT
outsole.**

CrewGuard® Sizes	XXS	XS	S	S+	M	M+	L	XL	XXL
STYLE 53: Men's	-	35-37	37-38	39-41	41-42	43-44	44-45	46-48	49-51
STYLE 53: Women's	32-34	35-38	38-39	40-42	42-43	44-45	-	-	-
STYLE 67014 Men/Women	-	-	34-37	-	38-41	-	42-45	46-48	-

Above chart is an indication ONLY, depending on the type of footwear worn, this can vary

Slip Resistance Test EN ISO 13287:2012, performed by TÜV Rheinland LGA Products GmbH in Leipzig, Germany during August 2018* On a scale where 0.0 is the absence of friction and 1.0 is very high friction (e.g. dry carpet), SFC rated .63 - more than tripling the .18 minimum standard. All SFC shoes use the Shoes For Crews patented slip-resistant outsole. Product tested: DOLCEB1 76236

CREWGUARD® - DATA GUIDE

Certification: EN ISO 20345:2011 (SB SRC)

Upper Material: Rubber

Lining Material: Rubber

Midsole Material: N/A

Outsole Material: Rubber

Safety Toe Cap: Steel

COO: China